

High Pressure Oval Gear Meters Overview



These compact rugged oval gear flowmeters are designed to give high performance with a low cost of ownership. These meters are happy measuring simple water like products as well as lubricating fluids. The standard inlet and outlet are BSP or NPT female threads for autoclave, flanges are also available. For OEM use alternatives, including manifold mountings, are available. The standard models are 316 St St, and other materials are available if required. For hazardous areas either the Namur sensor or the reed switch (simple apparatus) may be used.



FEATURES

- Excellent chemical resistance
- Rugged construction
- Individual calibration
- High viscosity capability
- Low pressure loss
- No flow conditioning required
- Compact meter assembly
- Hall, reed switch or Namur sensor
- Good accuracy
- 0.1% repeatability
- IP67/NEMA 4 protection
- Up to 700Bar on selected models
- Non-metallic option



IDEAL FOR

- Engine test
- Oil flow
- High viscosity fluids
- OEM equipment
- Hazardous areas



Ordering codes

Model
The order code is preceded by the flow meter size eg OG4
Body material
S = 316 St St
Temp rating
S = 80°C / 158°F
T = 100°C / 212°F
U = 150°C / 300°F
Pressure rating
5 = 50 Bar 750 PSI (St St)
4 = 400 Bar 5880 PSI (St St) (OG1-OG6)
7 = 700 Bar 10150 PSI (St St) (OG1-OG4)
Seal Material
V = Viton®
N = Nitrile
E = EPDM
K = Kalrez®
Detector Type
H = Hall Effect
R = Reed Switch & Resistor
N = Namur
X = Reed Switch
Pipe Thread
Q = 1/4"
H = 1/2"
T = 3/4"
U = 1"
P = 1 1/2"
D = 2"
Connections
B = BSP F
N = NPT F
* Autoclave and other high pressure fittings available

e.g. **OG4-SS4-VHT-B** is a standard flowmeter with an oil flow range of 0.25 to 50 L/min, 316 St St body, 400 Bar pressure rating, Viton® seal, Hall effect detector and 3/4" BSP female fittings with a standard 6 point traceable water calibration.



TECHNICAL SPECIFICATIONS

Model	Oil flow			Water flow			'K' factor
	Min	Max	Accuracy	Min	Max	Accuracy	Pulses/L
OG1	0.01	1	0.75% FSD	0.1	1	1.00% FSD	2050
OG2	0.03	4	0.75% FSD	0.15	4	1.00% FSD	1100
OG3	0.05	10	1%	0.5	10	0.50% FSD	400
OG4	0.25	50	0.50%	2.5	50	1.00%	100
OG5	0.50	100	0.50%	4	100	0.75%	70
OG6	2	200	0.50%	10	200	1.00%	21

At the heart of the meter are a pair of toothed oval gears one of which contains chemically resistant magnets.

Rotation is detected through the chamber wall by a Hall Effect detector, Namur sensor or a reed switch giving a number pulses per litre passed. The output is an NPN pulse or a voltage free contact closure either of which is readily interfaced with most electronic display or recording devices.

This combination of materials and technology ensures a long life product with reliable, accurate operation throughout. PEEK is a superb material for gear and bearing manufacture, it has excellent pressure and velocity characteristics coupled with very good thermal properties and chemical resistance. Stainless gears with roller bearings are an alternative.

For fluids with viscosities above 1000 cSt specially cut gears are required and the flow range is reduced for a given meter size.

Standard Materials of Construction

Body and cap	- 316 St St
'O' Ring seal	- Viton®
Gears	- PEEK
Magnets	- Ceramic

TITAN ENTERPRISES LTD.

Coldharbour Business Park, Sherborne, Dorset DT9 4JW

Tel: **(44) 01935 812790**

Email: sales@flowmeters.co.uk

www.flowmeters.co.uk

For reference only; for latest information contact your local distributor.